


Kegelager

39575-39520-TIMKEN - 39575-39520-TIMKEN

<https://www.123kogellager.be/kogellager-behuizing/rollager/kegellager/39575-39520-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS



| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | |
|--------------------|---------|---------|---------------------------------------|-------------------------|---------------------------------------|--------------------------------------|-----------------------|-------|-------------|-------|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁ | Factor ⁽²⁾ e | Dynamic ⁽¹⁾ C ₂ | Factor ⁽²⁾ e ₂ | Static C ₃ | Inner | Outer | |
| mm | mm | mm | N | | N | N | N | | | |
| 58.000 | 112.712 | 30.162 | 167000 | 2.34 | 42000 | 20300 | 1.12 | 23000 | 29575 | 29520 |
| 2.0000 | 4.4375 | 1.1975 | 25000 | | 9300 | 5000 | | 50000 | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight | |
|--------------------|---------|--------------------------|--|--------------------------------------|--|--------------------------------------|-------------------------------|-------------------------------|----------------|------------------|----------------|------|----------------|------|
| Shaft | | Housing | | Cage | | | | | G ₁ | G ₂ | C ₁ | | | |
| Width B | Width C | ER. Dr. a ⁽¹⁾ | Max Shaft Fillet Radius R ⁽¹⁾ | Backing Shoulder Dia. d ₁ | Max Housing Fillet Radius r ⁽¹⁾ | Backing Shoulder Dia. D ₁ | A ₁ ⁽¹⁾ | A ₂ ⁽¹⁾ | | | | | | |
| 30.162 | 23.812 | -6.6 | 3.5 | 61.8 | 68.8 | 3.3 | 167.8 | 191.8 | 1.6 | 2.7 | 94.3 | 23.7 | 0.1024 | 1.50 |
| 1.1975 | 0.9375 | -0.26 | 0.14 | 2.40 | 2.88 | 0.13 | 4.21 | 2.98 | 0.06 | 0.11 | | | | 3.37 |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | TIMKEN |
| N° Ean13 | 3663952316413 |
| Binnendiameter | 50.8 mm |
| Buitendiameter | 112.712 mm |
| Dikte | 30.162 mm |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE