

Kegellager 4595-4536-TIMKEN - 4595-4536-TIMKEN

<https://www.123kogellager.be/kogellager-behuizing/rollager/kegellager/4595-4536-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS

| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | |
|--------------------|---------|---------|---------------------------------------|-------------------------|---------------------------------------|-------------------------|-----------------------|--------|-------------|------|
| Bore d | O.D. D | Width B | Dynamic ^{1/2} C ₁ | Factor ^{1/2} e | Dynamic ^{1/2} C ₂ | Factor ^{1/2} K | Static C ₂ | Inner | Outer | |
| mm | mm | mm | N | | N | | N | | | |
| 53.975 | 111.125 | 38.895 | 100000 | 0.34 | 40000 | 20000 | 1.74 | 237000 | 4536 | 4536 |
| 2.1250 | 4.3750 | 1.5313 | 42500 | | 15500 | 8000 | | 53500 | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight |
|--------------------|---------|--------------------------|--|--------------------------------------|--|--------------------------------------|-------------------------------|-------------------------------|----------------|------------------|----------------|--------|----------------|
| Shaft | | Housing | | Cage | | | | | G ₁ | G ₂ | C ₃ | | |
| Width B | Width C | ER. Dr. a ^{1/2} | Max Shaft Fillet Radius R ^{1/2} | Backing Shoulder Dia. d ₁ | Max Housing Fillet Radius r ^{1/2} | Backing Shoulder Dia. D ₁ | A ₁ ^{1/2} | A ₂ ^{1/2} | | | | | |
| 40.157 | 32.545 | -12.4 | 3.5 | 63.8 | 3.3 | 100.8 | 93.8 | 1.5 | 1.3 | 75.5 | 20.2 | 0.1027 | 1.80 |
| 1.5810 | 1.2813 | -0.49 | 0.14 | 2.48 | 0.13 | 3.94 | 3.68 | 0.06 | 0.05 | | | | 3.95 |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | TIMKEN |
| N° Ean13 | 3663952317007 |
| Binnendiameter | 53.975 mm |
| Buitendiameter | 111.125 mm |
| Dikte | 38.895 mm |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE