


Kegelager

74472-74850-TIMKEN - 74472-74850-TIMKEN

<https://www.123kogellager.be/kogellager-behuizing/rollager/kegelager/74472-74850-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS



| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | |
|--------------------|---------|---------|---------------------------------------|-------------------------|---------------------------------------|--------------------------------------|-----------------------|--------|-------------|--|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁ | Factor ⁽²⁾ e | Dynamic ⁽¹⁾ C ₂ | Factor ⁽²⁾ e ₂ | Static C ₃ | Inner | Outer | |
| mm | mm | mm | N | | N | N | N | | | |
| 119.964 | 215.900 | 47.625 | 302000 | 1.23 | 99000 | 82000 | 1.20 | 914000 | 34472 | |
| 4.7230 | 8.5300 | 1.8750 | 89500 | | 22300 | 18800 | | 128000 | 34802 | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight | |
|--------------------|--------|--------------------------|---|---|---|---|-------------------------------|-------------------------------|----------------|------------------|----------------|------|----------------|-------|
| Width B | | ER. Dr. α ⁽¹⁾ | Shaft | | Housing | | Cage | | G ₁ | G ₂ | C ₁ | | | |
| mm | mm | mm | Max Shaft Fillet Radius R ₁ ⁽¹⁾ | Backing Shoulder Dia. d _s ⁽¹⁾ | Max Housing Fillet Radius r ₁ ⁽¹⁾ | Backing Shoulder Dia. D _s ⁽¹⁾ | A ₁ ⁽¹⁾ | A ₂ ⁽¹⁾ | | | | mm | mm | mm |
| 47.625 | 94.905 | 2.3 | 3.5 | 136.0 | 142.0 | 3.3 | 208.0 | 196.0 | 4.8 | 2.8 | 362.9 | 66.5 | 0.1338 | 3.47 |
| 1.8750 | 1.3750 | 0.09 | 0.14 | 5.35 | 5.59 | 0.13 | 8.19 | 7.72 | 0.18 | 0.09 | | | | 16.47 |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | TIMKEN |
| N° Ean13 | 3663952324807 |
| Binnendiameter | 119.964 mm |
| Buitendiameter | 215.9 mm |
| Dikte | 47.625 mm |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE