

Kegelager 46790A-46720-TIMKEN - 46790A-46720-TIMKEN

<https://www.123kogellager.be/kogellager-behuizing/rollager/kegelager/46790a-46720-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS

| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | |
|--------------------|---------|---------|---------------------------------------|-------------------------|---------------------------------------|-------------------------|-----------------------|--------|-------------|--|
| Bore d | O.D. D | Width T | Dynamic ⁽¹⁾ C ₁ | Factor ⁽²⁾ e | Dynamic ⁽¹⁾ C ₂ | Factor ⁽³⁾ K | Static C ₀ | Inner | Outer | |
| mm | mm | mm | N | | N | | N | | | |
| 165.100 | 225.425 | 41.275 | 302000 | 0.30 | 18000 | 1.52 | 629000 | 46790A | 46720 | |
| 6.5000 | 8.8750 | 1.6250 | 68200 | | 17700 | | 143000 | | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight | |
|--------------------|---------|--------------------------|--|--------------------------------------|--|--------------------------------------|-------------------------------|-------------------------------|----------------|------------------|----------------|-------|----------------|-------|
| Shaft | | Housing | | Cage | | | | | G ₁ | G ₂ | C ₃ | | | |
| Width B | Width C | ER. Dr. a ⁽¹⁾ | Max Shaft Fillet Radius R ⁽¹⁾ | Backing Shoulder Dia. d ₁ | Max Housing Fillet Radius r ⁽¹⁾ | Backing Shoulder Dia. D ₁ | A ₁ ⁽¹⁾ | A ₂ ⁽¹⁾ | | | | | | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | kg | |
| 38.688 | 33.338 | 2.5 | 0.8 | 174.0 | 195.6 | 3.3 | 218.8 | 295.0 | 3.8 | 2.8 | 572.0 | 174.7 | 0.1422 | 4.53 |
| 1.5225 | 1.3125 | 0.10 | 0.31 | 6.85 | 7.44 | 0.13 | 8.58 | 8.23 | 0.15 | 0.09 | | | | 10.00 |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | TIMKEN |
| N° Ean13 | 3663952326214 |
| Binnendiameter | 165.1 mm |
| Buitendiameter | 225.425 mm |
| Dikte | 41.275 mm |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE