


## Kogellager enkele rij ZKLN1034-2Z-INA - ZKLN1034-2Z-INA


<https://www.123kogellager.be/kogellager-behuizing/kogellager/enkele-rij/zkln1034-2z-ina>

**Axial angular contact ball bearings ZKLN1034-2Z**  
double direction, gap seals on both sides



d	10 mm	Tolerance: -0.005
D	34 mm	Tolerance: -0.010
B	20 mm	Tolerance: -0.25
	60 °	Contact angle
D <sub>u,max</sub>	28 mm	
d <sub>u</sub>	21 mm	
d <sub>u,rot</sub>	14 mm	
r <sub>1,rot</sub>	0,6 mm	
r <sub>2,rot</sub>	0,3 mm	
m	0,1 kg	Mass
C <sub>u</sub>	13400 N	Basic dynamic load rating, axial
C <sub>0u</sub>	16000 N	Basic static load rating, axial
n <sub>lim,grease</sub>	6000 1/min	Limiting speed for grease lubrication
M <sub>fr,rot</sub>	0,08 Nm	Bearing frictional torque
M <sub>fr</sub>	0,25 Nm	Axial rigidity
α <sub>cr</sub>	25 Nm/rad	Tilting rigidity
M <sub>r</sub>	0,029 kg x cm <sup>2</sup>	Mass moment of inertia for rotating inner ring
r <sub>ax</sub>	2 μm	Axial runout
		The axial runout data for screw drive bearing arrangements are based on the rotating inner ring.
ZM10		Designation of recommended INA locknut
		Locknuts not included in delivery.
M <sub>s</sub>	8 Nm	Tightening torque
		Only valid in conjunction with INA precision locknuts
F <sub>ax</sub>	4891 N	Axial preload force

Design of adjacent construction



Design of adjacent construction

### PRODUCTKENMERKEN

Merk	INA
N° Ean13	3663952334837
Binnendiameter	10 mm
Waterdicht maken	Flens aan beide zijden
Buitendiameter	34 mm
Dikte	20 mm
Gewicht	100 g
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE