




Kogellager enkele rij ZKLN1747-2Z-INA - ZKLN1747-2Z-INA

<https://www.123kogellager.be/kogellager-behuizing/kogellager/enkele-rij/zkln1747-2z-ina>

Axial angular contact ball bearings ZKLN1747-2Z
double direction, gap seats on both sides

d	17 mm	Tolerance: -0,006
D	47 mm	Tolerance: -0,010
B	25 mm	Tolerance: -0,20
α	60 °	Contact angle
D_{1max}	37 mm	
d₁	30 mm	
d_{1min}	23 mm	
r_{1max}	0,6 mm	
r_{1min}	0,3 mm	
m	0,22 kg	Mass
C_a	18500 N	Basic dynamic load rating, axial
C_{0a}	31000 N	Basic static load rating, axial
n_{0 grease}	6600 1/min	Limiting speed for grease lubrication
M_{fr}	0,92 Nm	Bearing frictional torque
C_a	450 N/μm	Axial rigidity
α₀	60 Nm/rad	Tilting rigidity
M_r	0,132 kg x cm ²	Mass moment of inertia for rotating inner ring
	2 μm	Axial runout
		The axial runout data for screw drive bearing arrangements are based on the rotating inner ring.
	ZM17	Designation of recommended INA locknut
	AM17	Designation of recommended INA locknut
		Locknuts not included in delivery.
M_s	15 Nm	Tightening torque
		Only valid in conjunction with INA precision locknuts
	7157 N	Axial preload force

PRODUCTKENMERKEN

Merk	INA
N° Ean13	3663952334868
Binnendiameter	17 mm
Waterdicht maken	Flens aan beide zijden
Buitendiameter	47 mm
Dikte	25 mm
Gewicht	220 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE