

Kogellager enkele rij ZKLN4090-2Z-INA - ZKLN4090-2Z-INA

<https://www.123kogellager.be/kogellager-behuizing/kogellager/enkele-rij/zkln4090-2z-ina>

Axial angular contact ball bearings ZKLN4090-2Z
Outside direction, gap seals on both sides

d	40 mm	Tolerance: -0.005
D	90 mm	Tolerance: -0.01
B	46 mm	Tolerance: -0.25
α	60 °	Contact angle
D_{5max}	80 mm	
d₁	65 mm	
d_{2min}	56 mm	
r_{1min}	0.6 mm	
r_{2min}	0.6 mm	
m	0.95 kg	Hoofdgewicht
C₁₀	22000 N	Basic dynamic load rating, axial
C₀₂	48000 N	Basic static load rating, axial
n_{lim} grease	3100 1/min	Limiting speed for grease lubrication
M_{fr}	0.65 Nm	Bearing frictional torque
C₁₀	1200 N/mm	Axial rigidity
C₀₂	750 N/mmrad	Tilting rigidity
M₀₂	5.5 kg x cm ²	Mass moment of inertia for rotating inner ring
r_{ax}	2.5 μm	Axial runout
		The axial runout data for screw drive bearing arrangements are based on the rotating inner ring.
	ZMA40B2	Designation of recommended INA locknut
	AMA40	Designation of recommended INA locknut
		Locknuts not included in delivery.
M₁₀	110 Nm	Tightening torque
		Only valid in conjunction with INA precision locknuts
	25185 N	Axial preload force

PRODUCTKENMERKEN

Merk	INA
N° Ean13	3663952334936
Binnendiameter	40 mm
Waterdicht maken	Flens aan beide zijden
Buitendiameter	90 mm
Dikte	46 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE