




Kogellager enkele rij ZKLN70120-2Z-INA - ZKLN70120-2Z-INA

<https://www.123kogellager.be/kogellager-behuizing/kogellager/enkele-rij/zkln70120-2z-ina>

Axial angular contact ball bearings ZKLN70120-2Z
double direction, gap seats on both sides

d	70 mm	Tolerance: -0.008
D	120 mm	Tolerance: -0.015
B	45 mm	Tolerance: -0.25
α	60 °	Contact angle
D_{1max}	110 mm	
d_1	95 mm	
d_2	92 mm	
r_{1max}	0.6 mm	
r_{2max}	0.6 mm	
m	2.4 kg	Mass
C_a	85000 N	Basic dynamic load rating, axial
C_{0a}	281000 N	Basic static load rating, axial
$n_{0,grease}$	2300 1/min	Limiting speed for grease lubrication
M_{fr}	1.2 Nm	Bearing frictional torque
S_a	1400 N/mm	Axial rigidity
c_a	2250 Nm/rad	Tilting rigidity
$M_{0.2}$	19.8 kg x cm ²	Mass moment of inertia for rotating inner ring
r_a	3 µm	Axial runout
		The axial runout data for screw drive bearing arrangements are based on the rotating inner ring.
ZMA70110		Designation of recommended INA locknut
AM70		Designation of recommended INA locknut
		Locknuts not included in delivery.
M_t	130 Nm	Tightening torque
		Only valid in conjunction with INA precision locknuts
	19171 N	Axial preload force

PRODUCTKENMERKEN

Merk	INA
N° Ean13	3663952334974
Binnendiameter	70 mm
Waterdicht maken	Flens aan beide zijden
Buitendiameter	120 mm
Dikte	45 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE