


Kogellager enkele rij ZKLN80130-2Z-INA - ZKLN80130-2Z-INA


<https://www.123kogellager.be/kogellager-behuizing/kogellager/enkele-rij/zkln80130-2z-ina>

Axial angular contact ball bearings ZKLN80130-2Z
double direction, gap seats on both sides



d	80 mm	Tolerance: -0.008
D	130 mm	Tolerance: -0.015
B	45 mm	Tolerance: -0.25
	60 °	Contact angle
D_{0,max}	120 mm	
d₁	105 mm	
d₂	102 mm	
r_{1,max}	0,6 mm	
r_{2,max}	0,6 mm	
m	2,7 kg	Mass
C₀	91000 N	Basic dynamic load rating, axial
C_{0a}	26000 N	Basic static load rating, axial
n_{0,gre}	2700 1/min	Limiting speed for grease lubrication
M_{0,gre}	1,8 Nm	Bearing frictional torque
n_{0,oil}	3000 1/min	Limiting speed for oil lubrication
M_{0,oil}	1,8 Nm	Bearing frictional torque
C₀	3000 Nm/rad	Tilting rigidity
M₀	27,6 kg x cm ²	Mass moment of inertia for rotating inner ring
	3 µm	Axial runout
		The axial runout data for screw drive bearing arrangements are based on the rotating inner ring.
	ZMAR0120	Designation of recommended INA locknut
	AM80	Designation of recommended INA locknut
		Locknuts not included in delivery.
M₀	160 Nm	Tightening torque
		Only valid in conjunction with INA precision locknuts
M₀	20604 N	Axial preload force

Design of adjacent construction



Design of adjacent construction

PRODUCTKENMERKEN

Merk	INA
N° Ean13	3663952334981
Binnendiameter	80 mm
Waterdicht maken	Flens aan beide zijden
Buitendiameter	130 mm
Dikte	45 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE