

Kegelager

42362-42587-B-TIMKEN - 42362-42587-B-TIMKEN

<https://www.123kogellager.be/kogellager-behuizing/rollager/kegellager/42362-42587-b-timken>

TAPERED ROLLER BEARINGS

TYPE TSF

| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | | |
|--------------------|----------|-------------|------------------------------|----------------------------|---------------------------------|----------------------------|--------------|-------|-------------|-------|---------|
| Bore ϕ | O.D. D | Width T_1 | Dynamic ⁽¹⁾ C_1 | Factors ⁽²⁾ e | Dynamic ⁽¹⁾ C_{10} | Factors ⁽²⁾ e | Static C_2 | Inner | Outer | | |
| mm | mm | mm | N | | N | | N | | | | |
| 92.075 | 149.225 | 12.706 | 102000 | 0.14 | 1.22 | 42200 | 3500 | 1.10 | 241000 | 42362 | 42587-B |
| 3.6250 | 5.8750 | 0.5000 | 36000 | | 9400 | | 8000 | | 94000 | | |

| Bearing Dimensions | | | | | | Shaft | | | Housing | | Geometry Factors | | | Bearing Weight |
|--------------------|-----------|--------------------|---------------------|--------------------|-------------------------------|-----------------------------|-----------------------------|-----------------------------|---------|-------|------------------|--|------|----------------|
| Width B | Width C | Eff. Ctr. ϕ^R | Outer Ring Range D1 | Flange Width C_2 | Max Shaft Fillet Radius R^S | Backing Shoulder Dia. d_1 | Backing Shoulder Dia. d_2 | Backing Shoulder Dia. D_1 | G_1 | G_2 | C_3 | | kg | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | | | | | lbs. | |
| 28.971 | 28.968 | 3.0 | 194.681 | 0.308 | 3.3 | 101.0 | 107.0 | 152.0 | 126.7 | 37.2 | 0.1385 | | 3.66 | |
| 1.1406 | 1.1388 | 0.12 | 6.0888 | 0.2188 | 0.14 | 3.98 | 4.21 | 5.99 | | | | | 4.48 | |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | TIMKEN |
| N° Ean13 | 3663952339429 |
| Binnendiameter | 92.075 mm |
| Buitendiameter | 149.225 mm |
| Dikte | 28.971 mm |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE