

Kegellager

95525-95925-B-TIMKEN - 95525-95925-B-TIMKEN

<https://www.123kogellager.be/kogellager-behuizing/rollager/kegellager/95525-95925-b-timken>

TAPERED ROLLER BEARINGS

TYPE TSF

| Bearing Dimensions | | | | Load Ratings | | | | | | Part Number | |
|--------------------|-----------|------------|---|-----------------------------|---|-----------------------------|--------------------------|-------|-------|-------------|--|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁₀ | Factors ⁽²⁾ e | Dynamic ⁽¹⁾ C ₉₀ | Factors ⁽²⁾ K | Static C ₀ | Inner | Outer | | |
| mm | mm | mm | N | | N | | N | | | | |
| 133.350 | 234.950 | 25.400 | 42900 | 6.37 | 14300 | 10300 | 1.58 | 97000 | 95525 | 95925-B | |
| 5.250 | 9.250 | 1.000 | 14180 | 1.12 | 3070 | 2300 | | 26900 | | | |

| Bearing Dimensions | | | | | | | Shaft | | | Housing | | Geometry Factors | | | Bearing Weight |
|--------------------|------------|-------------------------------|------------------------------------|-----------------------------------|--|--|--|--|----------------|----------------|----------------|------------------|----------------|-------|----------------|
| Width B | Width C | Eff. Ctr. a ⁽¹⁾ | Outer Ring Range D ₁ | Flange Width C ₂ | Max Shaft File Radius R ⁽¹⁾ | Sealing Shoulder Dia. d ₁ | Sealing Shoulder Dia. d ₂ | Sealing Shoulder Dia. D ₁ | D ₁ | D ₂ | C ₁ | C ₂ | C ₃ | kg | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | | | | | |
| 63.500 | 49.212 | -14.0 | 248.900 | 11.112 | 0.7 | 186.0 | 186.0 | 212.0 | 403.0 | 58.4 | 0.1323 | 11.56 | | 25.43 | |
| 2.300 | 1.9375 | -0.55 | 9.8824 | 0.4375 | 0.38 | 5.83 | 6.34 | 8.34 | | | | | | | |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | TIMKEN |
| N° Ean13 | 3663952339986 |
| Binnendiameter | 133.35 mm |
| Buitendiameter | 234.95 mm |
| Dikte | 63.5 mm |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE