

Zich instellende kogellager 1226-M-FAG - 1226-M-FAG

<https://www.123kogellager.be/kogellager-behuizing/kogellager/zich-instellende/1226-m-fag>

Self-aligning ball bearings 1226-M
main dimensions to DIN 630

| | |
|-------------------|---|
| d | 130 mm |
| D | 230 mm |
| B | 46 mm |
| C ₁ | 0,8 mm The ball projection must be taken into consideration when designing the adjacent construction. |
| D ₁ | 200,1 mm |
| D _{1max} | 216 mm |
| d ₁ | 161,5 mm |
| d _{1min} | 144 mm |
| r _{1max} | 2,5 mm |
| r _{1min} | 3 mm |
| m | 8,67 kg Mass |
| C | 120000 N Basic dynamic load rating, radial |
| e | 0,19 |
| Y ₁ | 3,24 |
| Y ₂ | 0,02 |
| C ₀ | 50000 N Basic static load rating, radial |
| Y ₀ | 3,4 |
| n ₀₁ | 4500 1/min Limiting speed |
| n ₀₂ | 5400 1/min Reference speed |
| C _u | 2550 N Fatigue limit load, radial |

Ball projection C1

PRODUCTKENMERKEN

| | |
|----------------|----------------|
| Merk | FAG |
| N° Ean13 | 3663952345932 |
| Binnendiameter | 130 mm |
| Buitendiameter | 230 mm |
| Dikte | 46 mm |
| Gewicht | 8396 g |
| Verpakking | 1 |
| Standaard | Geen standaard |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE