


## Zich instellende kogellager 1209-K-TVH-C3-H209-FAG - 1209-K-TVH-C3-H209-FAG

<https://www.123kogellager.be/kogellager-behuizing/kogellager/zich-instellende/1209-k-tvh-c3-h209-fag>

**Self-aligning ball bearings 1209-K-TVH-C3 + H209**  
main dimensions to DIN 630 and DIN 5415, with tapered bore and adapter sleeve



$d_{min}$	40 mm
D	85 mm
B	19 mm
$B_{min}$	5 mm
e	12 mm
$D_i$	72.7 mm
$D_{o,max}$	78 mm
$D_o$	60 mm
d	45 mm
$d_i$	57.7 mm
$d_{o,max}$	52 mm
$d_{o,min}$	48 mm
I	33 mm
$F_{a,max}$	1 mm
H209	Mass, adapter sleeve
m	0,454 kg Mass
$m_i$	0,22 kg Mass, adapter sleeve
C	22000 N Basic dynamic load rating, radial
e	0,21
$Y_1$	3,04
$Y_2$	4,7
$C_0$	7300 N Basic static load rating, radial
$Y_0$	3,18
$n_L$	9000 1/min Limiting speed
$n_R$	11100 1/min Reference speed
$C_2$	455 N Fatigue limit load, radial

### PRODUCTKENMERKEN

Merk	FAG
N° Ean13	3663952346205
Binnendiameter	40 mm
Buitendiameter	85 mm
Dikte	19 mm
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE