



Zich instellende kogellager 1214-K-TVH-C3-H214-FAG - 1214-K-TVH-C3-H214-FAG

<https://www.123kogellager.be/kogellager-behuizing/kogellager/zich-instellende/1214-k-tvh-c3-h214-fag>

Self-aligning ball bearings 1214-K-TVH-C3 + H214
main dimensions to DIN 630 and DIN 5415, with tapered bore and adapter sleeve

d_{int}	60 mm
D	125 mm
B	24 mm
B_{min}	5 mm
c	14 mm
D_1	106,6 mm
$D_{1,max}$	116 mm
D_2	92 mm
d	70 mm
d_1	87,7 mm
$d_{1,max}$	79 mm
d_2_{min}	75 mm
d_2_{max}	41 mm
I	1,8 mm
$f_{a,max}$	1,8 mm
f_a	H214 Mess, adapter sleeve
m	1,23 kg Mess
m_1	0,63 kg Mess, adapter sleeve
C	35000 N Basic dynamic load rating, radial
e	0,19
Y_1	3,36
Y_2	5,21
C_{DP}	13700 N Basic static load rating, radial
Y_2	3,52
n_D	6000 1/min Limiting speed
n_B	7900 1/min Reference speed
C_F	800 N Fatigue limit load, radial

PRODUCTKENMERKEN

Merk	FAG
N° Ean13	3663952346250
Binnendiameter	60 mm
Buitendiameter	125 mm
Dikte	24 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE