

## Zich instellende kogellager 2320-M-FAG - 2320-M-FAG

<https://www.123kogellager.be/kogellager-behuizing/kogellager/zich-instellende/2320-m-fag>

**Self-aligning ball bearings 2320-M**  
main dimensions to DIN 630



|                    |  |
|--------------------|--|
| d                  | 100 mm                                     |
| D                  | 215 mm                                     |
| B                  | 73 mm                                      |
| D <sub>1</sub>     | 183 mm                                     |
| D <sub>0,max</sub> | 201 mm                                     |
| d <sub>1</sub>     | 130,8 mm                                   |
| d <sub>0,max</sub> | 114 mm                                     |
| f <sub>a,max</sub> | 2,5 mm                                     |
| f <sub>res</sub>   | 3 mm                                       |
| m                  | 12,9 kg Mass                               |
| C                  | 195000 N Basic dynamic load rating, radial |
| e                  | 0,38                                       |
| Y <sub>1</sub>     | 1,67                                       |
| Y <sub>2</sub>     | 2,98                                       |
| C <sub>0</sub>     | 76000 N Basic static load rating, radial   |
| Y <sub>0</sub>     | 1,75                                       |
| n <sub>0</sub>     | 4500 1/min Limiting speed                  |
| n <sub>B</sub>     | 5200 1/min Reference speed                 |
| C <sub>10</sub>    | 3900 N Fatigue limit load, radial          |

### PRODUCTKENMERKEN

|                |               |
|----------------|---------------|
| Merk           | FAG           |
| N° Ean13       | 3663952350325 |
| Binnendiameter | 100 mm        |
| Buitendiameter | 215 mm        |
| Dikte          | 73 mm         |
| Verpakking     | 1             |

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE