

Naaldhulslager
TLAM1812-IKO - TLAM1812-IKO

https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/tlam1812-iko



SHELL TYPE NEEDLE ROLLER BEARINGS



Identification number											
Shaft dia. mm	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g	
18	---	---	---	---	---	---	TLAM 1812	13.7	---	---	---
Boundary dimensions mm											
Standard mounting dimensions mm											
Shaft dia. mm											
Housing bore dia. mm											
Basic dynamic load rating C N											
Basic static load rating C ₀ N											
Allowable rotational speed ^(*) rpm											
Assembled inner ring											
F _w	D	C	f ₂	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.
18	24	12	1.3	18.000	17.989	---	---	23.993	23.972	8 230	11 500
IRT 1512											

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952352978
Binnendiameter	18 mm
Buitendiameter	24 mm
Dikte	12 mm
Verpakking	1

contact@123kogellager.be
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE