


Naaldhulslager TA6030-Z-IKO - TA6030-Z-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/ta6030-z-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS



TA--Z TLA--Z

Shaft dia. mm	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
60	TA	6030 Z	191	---	---	---	---	---	---	---

Boundary dimensions mm			Standard mounting dimensions mm						Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring	
F _w	D	C	Shaft dia. h6		Housing bore dia. H7		Housing bore dia. N7		N	N	rpm	IRT 5030	
			Max.	Min.	Max.	Min.	Max.	Min.					
60	72	30	3.4	60.000	59.981	72.018	71.988	---	---	66 300	139 000	5 000	IRT 5030

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952357409
Binnendiameter	60 mm
Buitendiameter	72 mm
Dikte	30 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE