



Naaldhulslager TAM5030-IKO - TAM5030-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/tam5030-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS

Shaft dia. mm	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
50			TAM	5030	178					

Boundary dimensions mm	Standard mounting dimensions mm						Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ^(*) rpm	Assembled inner ring				
	Shaft dia. H7	Shaft dia. h8	Housing bore dia. H7	Housing bore dia. h7	Max.	Min.								
F _w D C i ₂ Max.	50	62	30	3.4	50.000	49.984	62.018	61.988	—	—	59 500	114 000	6 500	IRT 4530

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 50% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952357461
Binnendiameter	50 mm
Buitendiameter	62 mm
Dikte	30 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE