


Naaldhulslager TAW6550-Z-IKO - TAW6550-Z-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/taw6550-z-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS



| Shaft dia. mm | Identification number | | | | | | | | | |
|------------------|-----------------------|------------------|------------|------------------|----------|------------------|------------|------------------|-----------------|------------------|
| | Standard | Mass (Ref.) g | Closed end | Mass (Ref.) g | Standard | Mass (Ref.) g | Closed end | Mass (Ref.) g | Grease retained | Mass (Ref.) g |
| 65 | TAW 6550 Z | 330 | — | — | — | — | — | — | — | — |

| Boundary dimensions mm | | | Standard mounting dimensions mm | | | | | | Basic dynamic load rating C | Basic static load rating C ₀ | Allowable rotational speed ^(*) | Assembled inner ring | |
|---------------------------|----|----|---------------------------------|--------|-------------------------|--------|-------------------------|------|-----------------------------------|---|---|-------------------------|----------|
| F _w | D | C | Shaft dia. h6 | | Housing bore dia. H7 | | Housing bore dia. N7 | | N | N | rpm | IRT 5550 | |
| | | | Max. | Min. | Max. | Min. | Max. | Min. | | | | | |
| 65 | 77 | 50 | 3.4 | 65.000 | 64.981 | 77.018 | 76.988 | — | — | 101 000 | 246 000 | 4 000 | IRT 5550 |

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | IKO |
| N° Ean13 | 3663952357515 |
| Binnendiameter | 65 mm |
| Buitendiameter | 77 mm |
| Dikte | 45 mm |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE