

Kegelager

LM119348-LM119311D-TIMKEN - LM119348-LM119311D-TIMKEN

<https://www.123kogellager.be/kogellager-behuizing/rollager/kegelager/lm119348-lm119311d-timken>

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TDO

TYPE TDO

| Bearing Dimensions | | | | Load Ratings | | | | | | | | | | |
|--------------------|---------|---------|---------------------------|------------------------|-----------------|-----------------------|----------------|------------------------|-----------------|-----------------------|-------|------|--|--|
| Bore d | O.D. D | Width T | Double Outer Ring Width C | Dynamic ⁽¹⁾ | | Static ⁽²⁾ | | Dynamic ⁽³⁾ | | Factor ⁽⁴⁾ | | | | |
| mm | mm | mm | mm | C ₁₀ | C ₉₀ | Y ₁ | Y ₂ | C ₁₀ | C ₅₀ | C ₁₀₀ | K | | | |
| 95.25 | 136.525 | 68.26 | 67.19 | 36500 | 34000 | 0.28 | 2.28 | 3.54 | 36200 | 17800 | 63000 | 2.08 | | |
| 3.750 | 5.3750 | 2.6914 | 2.2500 | | | | | | 8740 | 3950 | 14200 | | | |

| Part Number | | Shaft | | | | Housing | | | | Pin | | Geometry Factors | | | Bearing Weight |
|-------------|-----------|---|--------------------------------------|---|--------------------------------------|----------------|----------------|----------------|----------------|----------------|------|------------------|----|------|----------------|
| Inner | Outer | Max. Shaft Fillet Radius R ₁ | Backing Shoulder Dia. d ₁ | Max. Housing Fillet Radius r ₁ | Backing Shoulder Dia. D ₁ | K ₁ | K ₂ | G ₁ | G ₂ | C ₁ | | | | | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | kg | |
| LM119348 | LM119311D | 2.3 | 195.8 | 0.8 | 131.8 | - | - | 148.4 | 84.1 | 0.1213 | 2.85 | | | 6.52 | |
| | | 0.05 | 4.13 | 0.05 | 5.18 | | | | | | | | | | |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | TIMKEN |
| N° Ean13 | 3663952358697 |
| Binnendiameter | 95.25 mm |
| Buitendiameter | 136.525 mm |
| Dikte | 68.26 mm |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE