


Naaldhulslager YB64-IKO - YB64-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/yb64-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g
9.525 ($\frac{3}{8}$)	—	—	—	—	YB 64	3.4	—	—	—

Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring
F_w	D	C	Shaft dia. h8	Housing bore dia. J7	Max.	Min.	N	N	rpm	
9.525 ($\frac{3}{8}$)	14.288 ($\frac{1}{2}$)	6.35 ($\frac{1}{4}$)	9.525 Max.	9.516 Min.	14.298 Max.	14.280 Min.	4 470	5 360	16 000	—

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952361239
Binnendiameter	9.525 mm
Buitendiameter	14.288 mm
Dikte	6.35 mm
Gewicht	3.4 g
Verpakking	1
Standaard	Geen standaard

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE