

Naaldhulslager YB910-IKO - YB910-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/yb910-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

Shaft dia. mm (inch)	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g	
14.288 ($\frac{9}{16}$)	—	—	—	—	—	—	—	—	YB 910 12.7	
Boundary dimensions mm(inch)		Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring	
F_w	D	C	Shaft dia. h8		Housing bore dia. J7	C	C_0	rpm		
14.288 $\frac{9}{16}$	19.050 $\frac{3}{4}$	15.881 $\frac{5}{8}$	Max. 14.286	Min. 14.277	Max. 19.062	Min. 19.041	14 300	26 700	11 000	—

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952361611
Binnendiameter	14.288 mm
Buitendiameter	19.05 mm
Dikte	15.88 mm
Gewicht	22 g
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE