


Naaldhulslager YBH108-IKO - YBH108-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/ybh108-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g		
15.875 ($\frac{5}{8}$)	—	—	—	—	—	—	—	—	YBH 108	15.3	
Boundary dimensions		mm(inch)		Standard mounting dimensions		mm		Basic dynamic load rating	Basic static load rating	Allowable rotational speed ^(*)	Assembled inner ring
F_w	D	C	b_2	Shaft dia. h8	Housing bore dia. J7	C	C_0	N	N	rpm	IRB 68-1
15.875 / $\frac{5}{8}$	22.225 / $\frac{7}{8}$	12.70 / .500	—	15.875 Max. Min.	15.864 / 22.237 Max. Min.	15 000	22 400	9 500	IRB 68-1		

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952361659
Binnendiameter	15.875 mm
Buitendiameter	22.225 mm
Dikte	12.7 mm
Gewicht	50 g
Verpakking	1
Standaard	Geen standaard

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE