



## Naaldhulslager BHAM1212-IKO - BHAM1212-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bham1212-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series

Shaft dia. mm (inch)	Identification number			Identification number			Mass (Ref.) g	Grease retained g	Mass (Ref.) g	
	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end				
19.050 ( $\frac{3}{4}$ )	—	—	—	—	—	—	BHAM 1212	28.5	—	—

Boundary dimensions			Standard mounting dimensions			Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring
F <sub>w</sub>	D	C	Shaft dia. h6 Max.   Min.	Housing bore dia. J7 Max.   Min.	mm				
19.050   $\frac{3}{4}$	26.988   $\frac{1}{2}$	19.05   $\frac{7}{16}$	1.3	19.050   19.037	27.000   26.979	16 600	22 600	20 000	IRB 612-1

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952361819
Binnendiameter	19.05 mm
Buitendiameter	26.988 mm
Dikte	19.05 mm
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE