



Naaldhulslager BHAM1412-IKO - BHAM1412-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bham1412-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
22.225 (7/8)	—	—	—	—	—	—	—	BHAM 1412	32.5	—	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic	Basic static	Allowable	Assembled
F_w	D	C	Shaft dia. ϕ	Housing bore dia. $J7$	Max.	Min.	load rating C	load rating C_0	rotational speed ⁽¹⁾	inner ring
mm	mm	mm	mm	mm	mm	mm	N	N	rpm	
22.225	30.162	19.05	22.225	22.212	30.176	30.151	18 000	26 100	18 000	IRB 1012

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952361871
Binnendiameter	22.225 mm
Buitendiameter	30.162 mm
Dikte	19.05 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE