


Naaldhulslager BHAM1614-IKO - BHAM1614-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bham1614-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g
25.400 (1)	—	—	—	—	—	—	—	—	—
								BHAM 1614	42.5

Boundary dimensions			Standard mounting dimensions				Basic dynamic	Basic static	Allowable	Assembled
F_w	D	C_1	Shaft dia. mm	Housing bore dia. mm	Shoulder dia. mm	Shoulder height mm	load rating C	load rating C ₀	rotational speed ^(*)	inner ring
Max.	Max.	Max.	Max.	Max.	Max.	Min.	N	N	rpm	
25.400	33.338	22.22	25.400	25.387	33.352	33.327	23 000	37 200	15 000	IRB 1214

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952362021
Binnendiameter	25.4 mm
Buitendiameter	33.338 mm
Dikte	22.22 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE