

Naaldhulslager

BHAM1616-IKO - BHAM1616-IKO

https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bham1616-iko

IKO

SHELL TYPE NEEDLE ROLLER BEARINGS

Inch Series



Shaft dia. mm (inch)	Identification number				Shaft dia. mm h8	Housing bore dia. mm J7	Basic dynamic load rating C N	Basic static load rating C0 N	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g						
25.400 (1)	—	—	—	—	—	—	BHAM 1616	48	—	—

Boundary dimensions			mm(inch)			Standard mounting dimensions			mm		
Fw	D	C	Max.	Min.	Max.	Min.	Max.	Min.	N	N	rpm
25.400	33.338	25.40	3.4	25.400	25.387	33.352	33.327	26 400	44 500	15 000	IRB 1216

Note⁽¹⁾

Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.

Remark

Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952362038
Binnendiameter	25.4 mm
Buitendiameter	33.338 mm
Dikte	25.4 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE