


## Naaldhulslager YB1612-IKO - YB1612-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/yb1612-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end										
25.400 (1)	—	—	—	—	—	—	—	—	—	—	—	YB 1612	34.5
Boundary dimensions			Standard mounting dimensions			Basic dynamic load rating C <sub>d</sub>	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(1)</sup>	Assembled inner ring				
F <sub>w</sub>	D	C	Shaft dia. h <sub>d</sub>	Housing bore dia. J7	Basic dynamic load rating C								
25.400	31.750	19.05	25.400	25.387	31.764	28 200	58 000	6 000	IRB 1212				

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952362052
Binnendiameter	25.4 mm
Buitendiameter	31.75 mm
Dikte	19.05 mm
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE