

## Naaldhulslager TAF11013040-IKO - TAF11013040-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/taf11013040-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER**  
Without Inner Ring

Shaft dia. mm	Identification number						Mass (Ref.) g
	RNA 49	RNA 69	RNA 48	TAF	TR	GTR	
110	—	—	—	<b>TAF 11013040</b>	—	—	880
Boundary dimensions mm		Standard needle diameter $D_1$ Max. mm	Basic dynamic load rating C N	Basic static load rating $C_0$ N	Allowable rotational speed <sup>(1)</sup> rpm		
$F_w$	D	C	$r_s$ (1)	125	134 000	324 000	3 500

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952369228
Binnendiameter	110 mm
Binnendiameter	4.331" inch
Buitendiameter	130 mm
Buitendiameter	5.118" inch
Dikte	40 mm
Dikte	1.575" inch
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE