


Kegelager

LM761649D-LM761610-TIMKEN - LM761649D-LM761610-TIMKEN

<https://www.123kogellager.be/kogellager-behuizing/rollager/kegelager/lm761649d-lm761610-timken>

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TDI

TYPE TDI



| Bearing Dimensions | | | | Load Ratings | | | | | | | | | |
|--------------------|---------|---------|---------------------------|-----------------------|--------|-----------------------|----------------|-----------------------|--------|-----------------------|--------|-----------------|------|
| Bore d | O.D. D | Width T | Double Inner Ring Width B | Dynamic ^{CR} | | Factors ^{CR} | | Dynamic ^{CR} | | Factors ^{CR} | | | |
| mm | mm | mm | mm | C ₁₀₂ | N | Y ₁ | Y ₂ | C ₉₀ | N | C ₅₀ | N | C ₁₀ | K |
| in | in | in | in | | | | | | | | | | |
| 343.052 | 457.098 | 122.238 | 122.238 | 100000 | 343052 | 0.5 | 1.4 | 2.1 | 257000 | 100000 | 413000 | 52900 | 1.24 |
| 13.506 | 17.996 | 4.8125 | 4.8125 | 38500 | 13506 | | | | 53400 | 43200 | 52900 | | |

| Part Number | | Dimensions | | | | Geometry Factors | | | Bearing Weight |
|-------------|----------|--|--------------------------------------|--|--------------------------------------|------------------|----------------|----------------|----------------|
| Inner | Outer | Max Shaft Fillet Radius r _s | Backing Shoulder Dia. d _s | Max Housing Fillet Radius r _h | Backing Shoulder Dia. D _s | G ₁ | G ₂ | C ₃ | kg |
| | | mm | mm | mm | mm | | | | lbm |
| LM761649D | LM761610 | 1.5 | 92.8 | 3.3 | 452.8 | 2206.4 | 322.3 | 0.1875 | 61.85 |
| | | 0.06 | 14.21 | 0.13 | 17.61 | | | | 136.66 |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | TIMKEN |
| N° Ean13 | 3663952370644 |
| Binnendiameter | 343.052 mm |
| Binnendiameter | 13.506" inch |
| Buitendiameter | 457.098 mm |
| Buitendiameter | 17.996" inch |
| Dikte | 122.238 mm |
| Dikte | 4 13/16" inch |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE