


Kegelager

LM961548D-LM961511-TIMKEN - LM961548D-LM961511-TIMKEN

<https://www.123kogellager.be/kogellager-behuizing/rollager/kegelager/lm961548d-lm961511-timken>

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TDI

TYPE TDI



| Bearing Dimensions | | | | Load Ratings | | | | | | | |
|--------------------|---------|---------|---------------------------|---------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|---------------------------------------|---------------------------------------|------------------------|--------|
| Bore d | O.D. D | Width T | Double Inner Ring Width B | Dynamic ^{CR} C ₁₀ | Static ^{CR} C ₀ | Factor ^{CR} Y ₁ | Factor ^{CR} Y ₂ | Dynamic ^{CR} C ₉₀ | Dynamic ^{CR} C ₅₀ | Factor ^{CR} K | |
| mm | mm | mm | mm | N | N | N | N | N | N | N | |
| 343.052 | 457.098 | 123.825 | 122.238 | 143000 | 322200 | 0.7 | 1.0 | 1.4 | 213000 | 260000 | 371900 |
| 13.5000 | 17.9960 | 4.8750 | 4.8125 | | | | | 48000 | 58500 | 83000 | |

| Part Number | | Dimensions | | | | Geometry Factors | | | Bearing Weight |
|-------------|----------|--|--------------------------------------|--|--------------------------------------|------------------|----------------|----------------|----------------|
| Inner | Outer | Max Shaft Fillet Radius r ₁ | Backing Shoulder Dia. d _s | Max Housing Fillet Radius r ₂ | Backing Shoulder Dia. D _s | G ₁ | G ₂ | C ₃ | kg |
| mm | mm | mm | mm | mm | mm | | | | lbs |
| LM961548D | LM961511 | 1.5 | 92.8 | 3.3 | 423.8 | 2261.5 | 386.4 | 0.2146 | 56.81 |
| | | 0.08 | 14.25 | 0.13 | 16.85 | | | | 125.04 |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | TIMKEN |
| N° Ean13 | 3663952370651 |
| Binnendiameter | 343.052 mm |
| Buitendiameter | 457.098 mm |
| Dikte | 123.825 mm |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE