

Naaldhulslager BRI61812-IKO - BRI61812-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bri61812-iko>



| Shaft dia. mm (inch) | Identification number | Mass (Ref.) g | Boundary dimensions mm(inch) | | | | | |
|------------------------------------|--------------------------|----------------------------------|----------------------------------|--|--------------------------|--------|--------------------------|--------------------|
| | | | d | D | C | B | F_w | S ⁽¹⁾ |
| 9.525 ($\frac{3}{8}$) | BRI 61812 | 67.5 | 9.525 $\frac{1}{2}$ | 28.575 (1 $\frac{1}{8}$) | 19.050 ($\frac{3}{4}$) | 19.300 | 15.875 ($\frac{1}{2}$) | 0.3 |
| Standard mounting dimensions mm | | ISO system load rating C | Specific load rating C_0 | Allowable rotational speed ⁽²⁾ rpm | Assembled inner ring | | | |
| d_s Min. | d_s Max. | | | | $r_{as max}$ | N | N | 25 000 |
| 14 | 14.5 | 24.5 | 0.6 | 18 900 | 19 700 | 25 000 | LRB 61012 | |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | IKO |
| N° Ean13 | 3663952375151 |
| Binnendiameter | 9.525 mm |
| Buitendiameter | 28.575 mm |
| Dikte | 19.3 mm |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE