

## Naaldhulslager BRI264120-IKO - BRI264120-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bri264120-iko>



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)					<sup>(1)</sup> S
			d	D	C	B	F <sub>w</sub>	
41.275 (1 5/8)	<b>BRI 264120</b>	410	41.275 (1 5/8)	65.088 (2 5/8)	31.750 (1 1/2)	32.000	50.800 (2 )	0.5
Standard mounting dimensions mm			ISO system load rating C	Specific load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring		
d <sub>s</sub> Min.	d <sub>s</sub> Max.	f <sub>as max</sub> (%)	N	N		LRB 263220		
48	49	57.8	1.5	63 200	118 000	8 000		

## PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952375373
Binnendiameter	41.275 mm
Buitendiameter	65.088 mm
Dikte	32 mm
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE