

## Naaldhulslager BRI284828-IKO - BRI284828-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bri284828-iko>



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)						
			$d$	$D$	$C$	$B$	$F_w$	$S$ <sup>(1)</sup>	
44.450 (1 3/4)	<b>BRI 284828</b>	855	44.450 (1 3/4)	76.200 3	44.450 (1 3/4)	44.700	57.150 (2 1/4)	1	
Standard mounting dimensions mm			ISO system load rating $C$	Specific load rating $C_0$	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring			
$d_s$ Min.	$d_s$ Max.	$r_{as\ max}$ Max.	N	N					
52.5	55	69	1.5	90 300	158 000	7 000	LRB 283624		

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952375397
Binnendiameter	44.45 mm
Buitendiameter	76.2 mm
Dikte	44.7 mm
Verpakking	-

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE