

## Naaldhulslager BRI406028-IKO - BRI406028-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bri406028-iko>

Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)						
			$d$	$D$	$C$	$B$	$F_w$	( <sup>1</sup> ) $S$	
<b>63.500</b> (2 1/2)	<b>BRI 406028</b>	1 130	63.500 (2 1/2)	95.250 (3 3/4)	44.450 (1 3/4)	44.700	76.200 (3)	1	
Standard mounting dimensions mm			ISO cyclic load rating $C$	ISO static load rating $C_0$	Allowable rotational speed( <sup>2</sup> )	Assembled inner ring			
$d_s$	$D_s$	$r_{as max}$	N	N	rpm	LRB 404828			
Min. 71	Max. 73	87	2	122 000	255 000	5 500			

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952375458
Binnendiameter	63.5 mm
Binnendiameter	2 1/2" inch
Buitendiameter	95.25 mm
Buitendiameter	3 3/4" inch
Dikte	44.7 mm
Dikte	1.76" inch
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE