

## Naaldhulslager BRI446828-IKO - BRI446828-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/bri446828-iko>



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)					
			$d$	$D$	$C$	$B$	$F_w$	$S$ <sup>(1)</sup>
<b>69.850</b> (2 3/4)	<b>BRI 446828</b>	1 520	69.850 (2 3/4)	107.950 (4 1/2)	44.450 (1 3/4)	44.700	82.550 (3 1/4)	1.5
Standard mounting dimensions mm			ISO system load rating $C$	Specific load rating $C_0$	Allowable rotational speed <sup>(2)</sup>	Assembled inner ring		
$d_s$	$D_s$	$r_{as\ max}$ <sup>(3)</sup>	$N$	$N$	rpm	LRB 445228		
Min.	Max.	Max.						
77	79	99.7	2	141 000	259 000	5 000		

## PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952375465
Binnendiameter	69.85 mm
Buitendiameter	107.95 mm
Dikte	44.7 mm
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE