


Naaldhulslager GBRI122416-IKO - GBRI122416-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/gbri122416-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
19.050 (3/4)	GBRI 122416	150	19.050 ₀ ⁰	38.100 ₀ ⁰	25.400 ₀ ⁰	25.650	25.400 ₀ ⁰

Standard mounting dimensions mm		Ball diam. mm C	Ball diam. mm C ₀	Allowable rotational speed (P) rpm	Assembled inner ring LRBZ 121616
d _a Min.	d _a Max.				
24	24.4	33.3	0.6	41 400	67 100

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952377421
Binnendiameter	19.05 mm
Buitendiameter	38.1 mm
Dikte	25.65 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE