


## Naaldhulslager GBRI203316-IKO - GBRI203316-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/gbri203316-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F <sub>w</sub>
<b>31.750</b> (1 1/4)	<b>GBRI 203316</b>	235	31.750 (1.250)	52.388 (2.063)	25.400 (1.000)	25.650	38.100 (1.500)

Standard mounting dimensions mm		Ball diam. mm C	Ball diam. mm C <sub>0</sub>	Allowable rotational speed (1) rpm	Assembled inner ring LRBZ 202416
d <sub>s</sub> Min. Max.	D <sub>s</sub> Max.				
37	37.1	47.3	0.6	54 200	97 700

Notes: (1) Maximum permissible corner radius of the housing.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. No grease is pre-applied. Perform proper lubrication.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952377469
Binnendiameter	31.75 mm
Buitendiameter	52.388 mm
Dikte	25.65 mm
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE