


Naaldhulslager GBRI203320-IKO - GBRI203320-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/gbri203320-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
31.750 (1 1/4)	GBRI 203320	291	31.750 (1) 0	52.388 (2) 0	31.750 (1) 0	32.000	38.100 (1) 0

Standard mounting dimensions mm		Ball diam. mm C	Ball rate load rating C ₀ N	Allowable rotational speed (P) rpm	Assembled inner ring LRBZ 202420		
d _s Min.	d _s Max.						
37	37.1	47.3	0.6	64 100	121 000	4 000	LRBZ 202420

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952377476
Binnendiameter	31.75 mm
Binnendiameter	1 1/4" inch
Buitendiameter	52.388 mm
Buitendiameter	2 1/16" inch
Dikte	32 mm
Dikte	1.26" inch
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE