


Naaldhulslager GBRI223520-IKO - GBRI223520-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/gbri223520-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			<i>d</i>	<i>D</i>	<i>C</i>	<i>B</i>	<i>F_w</i>
34.925 (1 3/8)	GBRI 223520	316	34.925 \pm 0.010	55.562 \pm 0.010	31.750 \pm 0.010	32.000	41.275 \pm 0.010

Standard mounting dimensions mm		Basic dynamic load rating <i>C</i> N	Static load rating <i>C₀</i> N	Allowable rotational speed (1) rpm	Assembled inner ring LRBZ 222620		
<i>d_a</i> Min.	<i>D_a</i> Max.						
40.2	40.2	50.5	0.6	67 000	130 000	3 500	

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-applied. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952377490
Binnendiameter	34.925 mm
Buitendiameter	55.562 mm
Dikte	32 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE