


Naaldhulslager GBRI264120-IKO - GBRI264120-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/gbri264120-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F_w
41.275 (1 5/8)	GBRI 264120	435	41.275 (1 5/8)	65.088 (2 5/8)	31.750 (1 1/4)	32.000	50.800 (2)
Standard mounting dimensions mm		Basic dynamic load (kg) C_0	Limiting static load rating C_0	Allowable rotational speed (°) rpm	Assembled inner ring		
d_a Min.	d_a Max.				r_{as} Max.	r_{as} Max.	r_{as} Max.
48	49	59.2	1	74 600	162 000	3 000	LRBZ 263220

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-applied. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952377544
Binnendiameter	41.275 mm
Buitendiameter	65.088 mm
Dikte	32 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE