

Naaldhulslager

GBR405224-IKO - GBR405224-IKO

https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/gbr405224-iko

IKO

MACHINED TYPE NEEDLE ROLLER BEARINGS

Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm ⁽¹⁾	
			F _d	D	C	D _s Max.	r _{as} max
63.500 (2 1/2)	GBR 405224	535	63.500 3/4	82.550 3/4	38.100 1 1/2	75.7	1.5
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾					
N	N	rpm					
120 000	248 000	2 500					

Notes⁽¹⁾

Maximum permissible corner radius of the housing.

⁽²⁾

Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.

Remarks:

2

No grease is preapplied. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952377575
Binnendiameter	63.5 mm
Buitendiameter	82.55 mm
Dikte	38.1 mm
Verpakking	1

contact@123kogellager.be
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE