


Naaldhulslager GBR486024-IKO - GBR486024-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/gbr486024-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm (¹⁾)	
			F _d	D	C	D _s Max.	r _{as max}
76.200 (3)	GBR 486024	630	76.200 ¹⁾	95.250 ¹⁾²⁾	38.100 ¹⁾²⁾	88	1.5
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ³⁾					
N	N	rpm					
131 000	298 000	2 000					

Notes:
1) Maximum permissible corner radius of the housing.
2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
2. The outer ring has an oil groove and an oil hole.
3. No grease is pre-packed. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952377612
Binnendiameter	76.2 mm
Buitendiameter	95.25 mm
Dikte	38.1 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE