


## Naaldhulslager GBR526828-IKO - GBR526828-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/gbr526828-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm ( <sup>(1)</sup> )	
			F <sub>a</sub>	D	C	D <sub>s</sub> Max.	r <sub>as</sub> max
<b>82.550</b> (3 1/4)	<b>GBR 526828</b>	1 100	82.550 ( <sup>(2)</sup> )	107.950 (4 1/4)	44.450 (1 3/4)	99.9	1.5
Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(3)</sup>					
N	N	rpm					
193 000	396 000	1 800					

Notes: <sup>(1)</sup> Maximum permissible corner radius of the housing.  
<sup>(2)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks: 2. The outer ring has an oil groove and an oil hole.  
3. No grease is pre-packed. Perform proper lubrication.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952377636
Binnendiameter	82.55 mm
Buitendiameter	107.95 mm
Dikte	44.45 mm
Verpakking	1

[contact@123kogellager.be](mailto:contact@123kogellager.be)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE