


Naaldhulslager GBR607632-IKO - GBR607632-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/gbr607632-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm ⁽¹⁾	
			F	D	C	D _s Max.	r _{as} max
95.250 (3 3/4)	GBR 607632	1 420	95.250 (3)	120.650 (4 7/8)	50.800 (2)	112.6	1.5
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾					
N	N	rpm					
228 000	522 000	1 600					

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952377667
Binnendiameter	95.25 mm
Buitendiameter	120.65 mm
Dikte	50.8 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE