


Naaldhulslager GBR648032-IKO - GBR648032-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/gbr648032-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



| Shaft dia. mm (inch) | Identification number | Mass (ref.) g | Boundary dimensions mm(inch) | | | Standard mounting dimensions mm (¹⁾) | |
|-----------------------------------|---|---|---------------------------------|-----------|----------|---|---------------------|
| | | | F | D | C | D _s Max. | r _{as max} |
| 101.600 (4) | GBR 648032 | 1 500 | 101.600 | 127.000.5 | 50.800.2 | 119 | 1.5 |
| Basic dynamic load rating C | Basic static load rating C ₀ | Allowable rotational speed(²⁾) | | | | | |
| N | N | rpm | | | | | |
| 237 000 | 556 000 | 1 500 | | | | | |

Notes:¹⁾ Maximum permissible corner radius of the housing.
²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | IKO |
| N° Ean13 | 3663952377674 |
| Binnendiameter | 101.6 mm |
| Buitendiameter | 127 mm |
| Dikte | 50.8 mm |
| Verpakking | 1 |

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE