


Naaldhulslager GBR142212-IKO - GBR142212-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/gbr142212-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm (⁽¹⁾)	
			F _o	D	C	D _s Max.	r _{as} max
22.225 (⁽²⁾ 7/8)	GBR 142212	71	22.225 ⁽³⁾	34.925 ⁽¹⁾	19.050 ⁽³⁾	30	0.6
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽⁴⁾					
N	N	rpm					
28 600	40 100	7 000					

Notes:⁽¹⁾ Maximum permissible corner radius of the housing.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952377711
Binnendiameter	22.225 mm
Binnendiameter	7/8" inch
Buitendiameter	34.925 mm
Buitendiameter	1 3/8" inch
Dikte	19.05 mm
Dikte	3/4" inch
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE