


Naaldhulslager GBRI325224-IKO - GBRI325224-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/gbri325224-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F_w
50.800 (2)	GBRI 325224	870	50.800 3	82.550 3 1/2	38.100 1 1/2	38.350	63.500 1 1/2

Standard mounting dimensions mm				Ball diam. mm ϕ	Ball diam. inch ϕ	Allowable rotational speed (1) rpm	Assembled inner ring
d_a Min.	d_a Max.	D_a Max.	$r_{as\ max}$ (1)				
58	61	75.7	1.5	120 000	248 000	2 500	LRBZ 324024

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952377896
Binnendiameter	50.8 mm
Buitendiameter	82.55 mm
Dikte	38.1 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE