


Naaldhulslager GBRI325228-IKO - GBRI325228-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/gbri325228-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
50.800 (2)	GBRI 325228	1 030	50.800 3	82.550 3 1/4	44.450 1 3/4	44.700	63.500 1 1/2

Standard mounting dimensions mm			Ball diam. mm C	Ball rate mm/ring C _g	Allowable rotational speed (°) rpm	Assembled inner ring LRBZ 324028
d _s Min.	d _s Max.	r _{as max} (°)				
58	61	75.7	1.5	141 000	306 000	2 500

Notes: (°) Maximum permissible corner radius of the housing.
(°) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952377902
Binnendiameter	50.8 mm
Binnendiameter	2" inch
Buitendiameter	82.55 mm
Buitendiameter	3 1/4" inch
Dikte	44.45 mm
Dikte	1 3/4" inch
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE