


Naaldhulslager GBRI365628-IKO - GBRI365628-IKO

<https://www.123kogellager.be/kogellager-behuizing/naaldlager/naaldhulslager/gbri365628-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F_w
57.150 (2 1/4)	GBRI 365628	1 130	57.150 (1) 1/2	88.900 (1) 1/2	44.450 (1) 1/2	44.700	69.850 (1) 1/2

Standard mounting dimensions mm				Basic dynamic load rating C_0	Static load rating C_0	Allowable rotational speed (1) rpm	Assembled inner ring
d_a	D_a	$r_{as max}$	r_{as} (1)				
Min.	Max.	Max.	N	N			
65	67	82	1.5	147 000	336 000	2 000	LRBZ 364428

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952377926
Binnendiameter	57.15 mm
Buitendiameter	88.9 mm
Dikte	44.45 mm
Verpakking	1

contact@123kogellager.be

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE